

360° DRINKERS

Corti Zootecnici's Drinkers



360° DRINKING LINE

Corti Zootecnici's 360° drinkers are specially designed to meet the water requirements of chicks of all genetics from the first hours of life. The design of the individual internal components of the drinker ensures that an optimal amount of water is delivered, facilitating watering even during the animals' life cycles under the most difficult conditions.



4004



- Reference flow rates at 20 cm column H2O: 40 cc/min
 - Reference flow rates at 60 cm column H2O: 100 cc/min
 - The use of the 'pressure level indicator' cup is recommended.
 - Broilers | Quails
- Turned version

4006I



- Reference flow rates at 20 cm column H2O: 50 cc/min
 - Reference flow rates at 60 cm column H2O: 140 cc/min
 - Discretionary use of drip cup
 - The use of the 'pressure level indicator' cup is recommended.
 - Broilers | Quails | Layers | Pullets | Breeders
- Available in turned version (4006 iLL)

4011HH



- Reference flow rates at 20 cm column H2O: 70 cc/min
- Reference flow rates at 60 cm column H2O: 190 cc/min
- The use of the 'pressure level indicator' cup is recommended.
- Laying hens | Broilers

4002R



- Reference flow rates at 20 cm column H2O: 28 cc/min
- Reference flow rates at 60 cm column H2O: 100 cc/min
- The use of the 'pressure level indicator' cup is recommended.
- Broilers | Pullets | Hens | Breeders

4006H



- Reference flow rates at 20 cm column H2O: 70 cc/min
 - Reference flow rates at 60 cm column H2O: 160 cc/min
 - Recommended use of the pressure level indicator in cold, temperate and humid climates
 - Broilers | Quails | Laying hens | Pullets
- Available in turned version (4006 HL)

4006HH



- Reference flow rates at 20 cm column H2O: 80 cc/min
 - Reference flow rates at 60 cm column H2O: 190 cc/min
 - The use of the 'pressure level indicator' cup is recommended.
 - Broilers | Quails | Laying hens | Pullets
- Available in turned version (4006 HHL)

4002HS



- Reference flow rates at 20 cm column H2O: 65 cc/min
- Reference flow rates at 60 cm column H2O: 160 cc/min
- The use of the 'pressure level indicator' cup is recommended.
- Laying birds | Ducks | Broilers

4002H



- Reference flow rates at 20 cm column H2O: 60 cc/min
 - Reference flow rates at 60 cm column H2O: 160 cc/min
 - Discretionary use of drip cup
 - Laying birds | Ducks | Broilers
- Available in turned version (4002 HL)

4002HH



- Reference flow rates at 20 cm column H2O: 65 cc/min
- Reference flow rates at 60 cm column H2O: 180 cc/min
- Pressure level indicator or drip cup required
- Broiler | Duck

4007H



- Reference flow rates at 20 cm column H2O: 35 cc/min
- Reference flow rates at 60 cm column H2O: 100 cc/min
- The use of the 'pressure level indicator' cup is recommended.
- Laying hens | Quails | Broilers

4007HH



- Reference flow rates at 20 cm column H2O: 34 cc/min
- Reference flow rates at 60 cm column H2O: 100 cc/min
- Discretionary use of drip cup
- The use of the 'pressure level indicator' cup is recommended.
- Broilers | Quails | Layers | Pullets | Breeders



DRINKERS 360°

The lightness of the 360° drinkers makes it easy to water the animals by ensuring that the water flow rate is delivered directly to the beak in proportion to each animal's needs, avoiding wastage.

The composition of the stainless steel parts makes the 360° drinkers durable under the most extreme conditions.



Use a **QR code reader** on your device to access our website.



Via Volta 4, Monvalle (VA) 21020, Italy
info@cortizootechnici.com | +39 0332 799 985 | www.cortizootechnici.it