











Û,

VERTICAL ACTION DRINKERS

Corti Zootecnici's vertical-only opening nipples are **specifically designed for layers and breeders.** Inox steel construction and precision machinery make Corti Zootecnici's vertical opening nipples sturdy and suited for many long years of operations in the field.

The proven and refined internal design of the nipples is key for the optimized and precise flow.



•

- Reference flow rate at 20 cm H2O: 40 ml/min
- Reference flow rate at 60 cm H2O: 100 ml/min
- The use of the "pressure level indicator"cup or the drip-cup or the water-through is required
- Caged Layers After Weaning |Breeders | Rabbits

4003



- Reference flow rate at 20 cm H2O: 40 ml/min
- Reference flow rate at 60 cm H2O: 100 ml/min
- The use of the "pressure level indicator" cup or the drip-cup or the water-through is required
- The rubber gasket is adaptable to different holes tolerance. Recommended for the recovery of damaged valve seat hole in the pipes.
- Caged Layers

4005R



- Reference flow rate at 20 cm H2O: 75 cc/min
- Reference flow rate at 60 cm H2O: 180 ml/min
- The use of the "pressure level indicator" cup or the drip-cup or the water-through is required
- Caged Layers
- Also available in yellow color (Ref. 4005 RG)



Use a **QR code** reader on your device to access our website.







Via Volta 4, Monvalle (VA) 21020, Italy info@cortizootecnici.com |+39 0332 799 985 | www.cortizootecnici.it

 \square \bigcirc f in